

A Proven Performer Recognized for Economical Installation



Manitowoc Public Library
Manitowoc, Wisconsin
ARCHITECT
Engberg Anderson Design Partnership, Milwaukee, Wisconsin
GLAZING CONTRACTOR
Sheboygan Glass Company, Inc., Sheboygan, Wisconsin
PHOTOGRAPHY
© Bob Freund

Taking center stage in Kawneer's lineup, the EnCORE™ Framing System is a two-piece face-and-gutter system that offers thermal economy, a structural silicone glazed (SSG) option and numerous design choices. Engineered for easy installation and lower costs, features include the unique QuickSeal™ self-sealing system, a broad selection of system depths and a 1-3/4" (44.5 mm) minimal sightline. The EnCORE™ Framing System readily adapts to remodel projects and new construction, whether traditional or modern architecture.

ECONOMY

EnCORE™ is a QuickSeal™ dry-glazed self-sealing framing system and is the first to eliminate joint sealant at horizontal joints, making it more cost effective. The vertical gasket runs through, and when "pinched" by the head, sill and intermediate horizontals, a watertight seal is created, eliminating the need for sealant.

By using the same extrusions for horizontal and vertical mullions, metal utilization is maximized. In addition, the tongue on the extrusions eliminates the need for a secondary, continuous water deflector, thus economizing on installation costs and time.

EnCORE™ Framing System also requires no setting block chair at intermediate horizontals. And at the sill, the system utilizes a simple setting block chair that fits snugly within the glazing pocket and requires no fastening. The system accepts standard 1" (25.4 mm) or 1/4" (6.4 mm) infills and can also be adapted to accept other infills in 1/8" (3.2 mm) increments.

The top-loaded glazing gaskets are the same as those used in the Kawneer flagship Trifab™ Framing Systems, which helps reduce field labor and minimize inventory requirements.

Providing single-source responsibility, Kawneer entrances, windows, curtain walls and slope glazing are compatible with the EnCORE™ Framing System.

PERFORMANCE

A specially engineered thermal clip eliminates metal-to-metal contact by snapping onto the mullion. The cover then snaps onto the clip for true thermal integrity. In addition, the clip has an extended leg on one side, which acts as a "w" block and prevents shifting of glass due to climate changes and building movement.

Engineered to meet or exceed certified performance requirements for air and water infiltration, the EnCORE™ Framing System has been fully tested according to ASTM E283 and ASTM E331. Thermal testing was completed in accordance with AAMA 1503.

The EnCORE™ Framing System also offers architects and building owners the ability to determine project-specific U-factors by referring to thermal tables in our architectural manual. Unique to Kawneer, these tables enable U-factor calculations for each project by utilizing the total glass percentage and the project's center of glass (COG) U-factor.


AESTHETICS

For additional freedom of expression, the EnCORE™ Framing System offers front or center glazing options. An SSG option is also available. And to provide greater design flexibility, the face-and-gutter system offers system depths of 3-9/16" (90.5 mm), 4-1/2" (114.3 mm) or 6" (152.4 mm) front glazed and 4-1/2" (114.3 mm) center glazed.

The 1-3/4" (44.5 mm) minimal sightline provides consistent design aesthetics, while a 1-1/4" (31.75 mm) perimeter sightline is also available. Since the exterior face and interior mullions are separate pieces, two-color design considerations are easily realized.



**Customer Service Center, Blue Cross and Blue Shield of Louisiana
Baton Rouge, Louisiana**
ARCHITECT
Architectural Group of Baton Rouge, Baton Rouge, Louisiana
GLAZING CONTRACTOR
Louisiana Glass Company, Baton Rouge, Louisiana
PHOTOGRAPHY
© Gordon Schenk



Another key feature of the EnCORE™ Framing System's separate components is that they are easily adapted to curved applications. The framing is available in three fabrication methods: screw spline, shear block or Type B, which is a combination of both.

FOR THE FINISHING TOUCH

Permanodic™ anodized finishes are available in Class I and Class II in seven different color choices.

Painted finishes, including fluoropolymer, that meet or exceed AAMA 2605 are offered in many standard choices and an unlimited number of specially designed colors.

Solvent-free powder coatings add the green element with high performance, durability and scratch resistance that meet the standards of AAMA 2604.