

Door: Insulated 1473 KANADA

Applications:

The 1473 Kanada door series is compatible with the frame sections of other thermal-break ranges, thus allowing the integration of doors in all ensembles, comprising fixed, French style and Italian style as well as more complex veranda-type projects.

Market:

- Multiple-occupancy or individual residences
- Verandas
- Non-residential
- New or refurbishing

Frame types:

Type of Opening	Number of Openings	
	1 Leaf	2 Leafs
Interior with flap	X	X
Interior with independent leaves		X
Exterior with flap	X	X
Exterior with independent leaves		X

Window aesthetics and choice of doorsteps:

Type of Opening	Type of Threshold	
	Flat Threshold	Seal Threshold
Opening Border	X	X
Opening with plinth	X	

Design:

Attractive and in harmony with other casement windows and sliding windows.

Adjustable supporting hinges for a finish of unbeatable quality.

Can accommodate all types of decorative or glazed panels.

Paint in all the colours of the RAL Label Qualicot range. Anodisation class 20 (natural shade, bronze, gold and stainless steel).

Window and casement joint in EPDM available in black and grey, harmonising with the colour of the door.

Windows can be painted in two colours.

100% compatible with the other Kawneer products.

Performance:

Thermal comfort

The openings are designed to accommodate padding of up to 39 mm, facilitating the integration of double-glazed windows with strong thermal insulation, anti-breakage or noise attenuation systems, with or without small pieces of wood built in.

Reinforced doorstep waterproofing.

Performance for air (A) water (E) wind (V): A*3 E*4B V*A2

It is possible to control the door in three dimensions to facilitate on-site maintenance..

Acoustic insulation:

-30 dB with glass 4/14/6

-35 dB with glass 44² silence/14/44² security