

Hurricane Resistant Window Product Selection Guide

	MODEL	DESIGN PRESSURE RATING (PSF POS.)	DESIGN PRESSURE RATING (PSF NEG.)	WATER PRESSURE TEST (PSF)	FRAME DEPTH	CONFIGURATION	TEST STANDARD	WIND ZONE	MISSILE DESIGNATION	TRIM / CLIP
hung										
SINGLE HUNG	19100	80	110	12	3-1/4"	O/X	TAS, ASTM	4	LM	S-1648 / S-1649
SINGLE HUNG	8400TL	90	90	15	4"	O/X	TAS, ASTM	4	SM / LM-D	
sliding										
HORIZONTAL SLIDING	8400TL	90	90	15	4"	OX	TAS, ASTM	4	SM / LM-D	
casement										
CASEMENT OUTSWING	AA™4325	80	80	15	3-1/4"	X, X/X, O/X	TAS, ASTM	4	SM / LM-D	
CASEMENT OUTSWING	NX-3100I	100	100	15	3-1/4"	X	TAS, ASTM	4	LM-D	S-1542 / S-1543
CASEMENT OUTSWING	GLASSvent™UT	90	90	15	4-3/8"/5-1/8"	X	TAS, ASTM	4	SM / LM-D	
projected										
PROJECTED OUT	8225TL	65	65	15	2-1/4"	X	TAS, ASTM	4	SM / LM-D	
PROJECTED OUT	AA™4325	80	80	15	3-1/4"	X, X/X	TAS, ASTM	4	SM / LM-D	
PROJECTED OUT	GLASSvent™UT	90	90	15	4-3/8"/5-1/8"	X	TAS, ASTM	4	SM / LM-D	
fixed / project out										
FIXED / PROJECT OUT	8225TL	100	130	15	2-1/4"	O/X	TAS, ASTM	4	SM	
FIXED / PROJECT OUT	8225TL	90	90	15	2-1/4"	O/X	TAS, ASTM	4	LM-D	
FIXED / PROJECT OUT	AA™4325	80	80	15	3-1/4"	O/X, O/X/X	TAS, ASTM	4	SM / LM-D	
FIXED / PROJECT OUT	NX-3510I	100	100	15	3-1/4"	O/X	TAS, ASTM	4	LM-D	
fixed										
FIXED	AA™4325	80	80	15	3-1/4"	O, O/O	TAS, ASTM	4	SM / LM-D	
FIXED	NX3800I	80	80	15	3-1/4"	O	TAS, ASTM	4	LM-D	S-1542 / S-1543