




1630 SS IR HURRICANE IMPACT OPTIONS			
	7-13/16" System	8-13/16" System	8-13/16" System with 1/2" x 5" Steel Bars
			
Design Pressure (DP)	up to 70 psf	up to 130 psf	up to 130 psf
Maximum Frame Spacing x Maximum Frame Height	63" x 132" @ 57psf 63" x 99" @ 70 psf	63" x 132" Single and Twin Span	63" x 167-3/4" Single and Twin Span
Maximum DLO (Width X Height)	60" x 93"	60" x 93"	60" x 93"
Zone 3 (Non-HVHZ)	1, 2, 3	use Zone 4	use Zone 4
Zone 4 (HVHZ) SMI - Level A	8, 9	8, 9	8, 9
Zone 4 (HVHZ) LMI - Level D	1, 2, 6, 7	1, 2, 4, 5, 6, 7	1, 2, 4, 5, 6, 7
Zone 4 (HVHZ) Level E	N/A	10	10
Doors	N/A	up to 8' Tall x 7' Wide Pair	up to 8' Tall x 7' Wide Pair

Refer to the Product Approvals for size, variations and restrictions based on the design pressures and interlayer options.

INTERLAYER KEY			
	Interlayer	DP	Glazing Method
1	0.090 DuPont PVB	70	Wet
2	0.090 Solutia PVB	70	Wet
3	0.060 DuPont SG	70	Dry
4	0.090 DuPont SG	90	Dry
5	0.120 DuPont SG	110	Dry
6	0.090 DuPont SG	130	Wet
7	0.077 Solutia VS02	130	Wet
8	0.060 DuPont PVB	130	Dry
9	0.060 Solutia PVB	130	Dry
10	0.180 DuPont SG	130	Dry

Laws and building and safety codes governing the design and use of glazed entrance, window, and curtain wall products vary widely. Kawneer does not control the selection of product configurations, operating hardware, or glazing materials, and assumes no responsibility therefor.

Kawneer reserves the right to change configuration without prior notice when deemed necessary for product improvement.
© Kawneer Company, Inc., 2015

Laws and building and safety codes governing the design and use of glazed entrance, window, and curtain wall products vary widely. Kawneer does not control the selection of product configurations, operating hardware, or glazing materials, and assumes no responsibility therefor.

Kawneer reserves the right to change configuration without prior notice when deemed necessary for product improvement.
© Kawneer Company, Inc., 2015