

Declare.™

250T/350T/500T Insulpour™ Thermal Entrances Kawneer Company, Inc.

Final Assembly: Bloomsburg, Pennsylvania, USA

Life Expectancy: 40+ Years

End of Life Options: Recyclable (85-95%), Landfill (5-15%)

Ingredients:

Frame: Anodized Aluminum; Thermal & Weathering: Bicyclo[2.2.1]Hept-2-Ene, 5-Ethylidene-, Polymer with Ethene and 1-Propene, Carbon black, Hydrated Magnesium Silicate, Polypropylene, White Mineral oil (Petroleum), 1-Propene, Polymer with Ethene, Polymethylene Polyphenyl Isocyanate, 4,4'-Methylenediphenyl Diisocyanate, Oxirane, Methyl-, Polymer with Oxirane, Ether with 1,2,3-Propanetriol (3:1), 1,3-Isobenzofurandione, Polymer with 2,2'-Oxybis[Ethanol], Calcium Carbonate, Calcium Oxide, Carbonic Dichloride, Polymer with 4,4'-(1-Methylethylidene)Bis[Phenol], Clay, Dicumyl-Peroxide, Diethylene Glycol, Poly[Oxy(Methyl-1,2-Ethanediy)], α,α',α'' - 1,2,3-Propanetriyltris[ω -Hydroxy-, Polyethylene, Propanol, Oxybis-, Zinc Oxide, Ethylene Glycol; Hardware: Stainless Steel, Iron, Zinc, Chromium, Metallic, Manganese, Nickel (Metallic), Copper, Silicon, Molybdenum, Cellulose, Ethyl Ether

Living Building Challenge Criteria:

KAW-1026

VOC Content: N/A

Declaration Status

EXP. 01 DEC 2020

VOC Emissions: N/A

LBC Red List Free

LBC Compliant

Declared

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ declareproducts.com

Declare.

250T/350T/500T Insulpour™ Thermal Entrances Kawneer Company, Inc.

Final Assembly: Kent, Washington, USA

Life Expectancy: 40+ Years

End of Life Options: Recyclable (85-95%), Landfill (5-15%)

Ingredients:

Frame: Anodized Aluminum; Thermal & Weathering: Bicyclo[2.2.1]Hept-2-Ene, 5-Ethylidene-, Polymer with Ethene and 1-Propene, Carbon black, Hydrated Magnesium Silicate, Polypropylene, White Mineral oil (Petroleum), 1-Propene, Polymer with Ethene, Polymethylene Polyphenyl Isocyanate, 4,4'-Methylenediphenyl Diisocyanate, Oxirane, Methyl-, Polymer with Oxirane, Ether with 1,2,3-Propanetriol (3:1), 1,3-Isobenzofurandione, Polymer with 2,2'-Oxybis[Ethanol], Calcium Carbonate, Calcium Oxide, Carbonic Dichloride, Polymer with 4,4'-(1-Methylethylidene)Bis[Phenol], Clay, Dicumyl-Peroxide, Diethylene Glycol, Poly[Oxy(Methyl-1,2-Ethanedyl)], α,α',α'' - 1,2,3-Propanetriyltris[ω -Hydroxy-, Polyethylene, Propanol, Oxybis-, Zinc Oxide, Ethylene Glycol; Hardware: Stainless Steel, Iron, Zinc, Chromium, Metallic, Manganese, Nickel (Metallic), Copper, Silicon, Molybdenum, Cellulose, Ethyl Ether

Living Building Challenge Criteria:

KAW-1025

VOC Content: N/A

Declaration Status

EXP. 01 DEC 2020

VOC Emissions: N/A

LBC Red List Free

LBC Compliant

Declared

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ declareproducts.com

Declare.™

250T/350T/500T Insulpour™ Thermal Entrances Kawneer Company, Inc.

Final Assembly: Lethbridge, Alberta, Canada

Life Expectancy: 40+ Years

End of Life Options: Recyclable (85-95%), Landfill (5-15%)

Ingredients:

Frame: Anodized Aluminum; Thermal & Weathering: Bicyclo[2.2.1]Hept-2-Ene, 5-Ethylidene-, Polymer with Ethene and 1-Propene, Carbon black, Hydrated Magnesium Silicate, Polypropylene, White Mineral oil (Petroleum), 1-Propene, Polymer with Ethene, Polymethylene Polyphenyl Isocyanate, 4,4'-Methylenediphenyl Diisocyanate, Oxirane, Methyl-, Polymer with Oxirane, Ether with 1,2,3-Propanetriol (3:1), 1,3-Isobenzofurandione, Polymer with 2,2'-Oxybis[Ethanol], Calcium Carbonate, Calcium Oxide, Carbonic Dichloride, Polymer with 4,4'-(1-Methylethylidene)Bis[Phenol], Clay, Dicumyl-Peroxide, Diethylene Glycol, Poly[Oxy(Methyl-1,2-Ethanediy)], α,α',α'' - 1,2,3-Propanetriyltris[ω -Hydroxy-, Polyethylene, Propanol, Oxybis-, Zinc Oxide, Ethylene Glycol; Hardware: Stainless Steel, Iron, Zinc, Chromium, Metallic, Manganese, Nickel (Metallic), Copper, Silicon, Molybdenum, Cellulose, Ethyl Ether

Living Building Challenge Criteria:

KAW-1027

VOC Content: N/A

Declaration Status

EXP. 01 DEC 2020

VOC Emissions: N/A

LBC Red List Free

LBC Compliant

Declared

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ declareproducts.com

Declare.

250T/350T/500T Insulpour™ Thermal Entrances Kawneer Company, Inc.

Final Assembly: Roselle, Illinois, USA

Life Expectancy: 40+ Years

End of Life Options: Recyclable (85-95%), Landfill (5-15%)

Ingredients:

Frame: Anodized Aluminum; Thermal & Weathering: Bicyclo[2.2.1]Hept-2-Ene, 5-Ethylidene-, Polymer with Ethene and 1-Propene, Carbon black, Hydrated Magnesium Silicate, Polypropylene, White Mineral oil (Petroleum), 1-Propene, Polymer with Ethene, Polymethylene Polyphenyl Isocyanate, 4,4'-Methylenediphenyl Diisocyanate, Oxirane, Methyl-, Polymer with Oxirane, Ether with 1,2,3-Propanetriol (3:1), 1,3-Isobenzofurandione, Polymer with 2,2'-Oxybis[Ethanol], Calcium Carbonate, Calcium Oxide, Carbonic Dichloride, Polymer with 4,4'-(1-Methylethylidene)Bis[Phenol], Clay, Dicumyl-Peroxide, Diethylene Glycol, Poly[Oxy(Methyl-1,2-Ethanedyl)], α,α',α'' - 1,2,3-Propanetriyltris[ω -Hydroxy-, Polyethylene, Propanol, Oxybis-, Zinc Oxide, Ethylene Glycol; Hardware: Stainless Steel, Iron, Zinc, Chromium, Metallic, Manganese, Nickel (Metallic), Copper, Silicon, Molybdenum, Cellulose, Ethyl Ether

Living Building Challenge Criteria:

KAW-1028

VOC Content: N/A

Declaration Status

EXP. 01 DEC 2020

VOC Emissions: N/A

LBC Red List Free

LBC Compliant

Declared

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ declareproducts.com

Declare.

250T/350T/500T Insulpour™ Thermal Entrances Kawneer Company, Inc.

Final Assembly: Vaughan, Ontario, Canada

Life Expectancy: 40+ Years

End of Life Options: Recyclable (85-95%), Landfill (5-15%)

Ingredients:

Frame: Anodized Aluminum; Thermal & Weathering: Bicyclo[2.2.1]Hept-2-Ene, 5-Ethylidene-, Polymer with Ethene and 1-Propene, Carbon black, Hydrated Magnesium Silicate, Polypropylene, White Mineral oil (Petroleum), 1-Propene, Polymer with Ethene, Polymethylene Polyphenyl Isocyanate, 4,4'-Methylenediphenyl Diisocyanate, Oxirane, Methyl-, Polymer with Oxirane, Ether with 1,2,3-Propanetriol (3:1), 1,3-Isobenzofurandione, Polymer with 2,2'-Oxybis[Ethanol], Calcium Carbonate, Calcium Oxide, Carbonic Dichloride, Polymer with 4,4'-(1-Methylethylidene)Bis[Phenol], Clay, Dicumyl-Peroxide, Diethylene Glycol, Poly[Oxy(Methyl-1,2-Ethanedyl)], α,α',α'' - 1,2,3-Propanetriyltris[ω -Hydroxy-, Polyethylene, Propanol, Oxybis-, Zinc Oxide, Ethylene Glycol; Hardware: Stainless Steel, Iron, Zinc, Chromium, Metallic, Manganese, Nickel (Metallic), Copper, Silicon, Molybdenum, Cellulose, Ethyl Ether

Living Building Challenge Criteria:

KAW-1029

VOC Content: N/A

Declaration Status

EXP. 01 DEC 2020

VOC Emissions: N/A

LBC Red List Free

LBC Compliant

Declared

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ declareproducts.com