

2250 L-R (Low-Rise) Wall System

The Low-rise System Designed
for No-compromise Performance,
Economy and Aesthetics



JcIT Institute of Technology, Englewood, CO
Architect: The Neenan Company, Fort Collins, Denver and Colorado Springs, CO
Glazing Contractor: Ken Caryl Glass, Inc., Littleton, CO

Today's construction industry demands faster building times, higher performance and improved aesthetics. In response, Kawneer's team of engineers developed 2250 L-R Wall System for low-rise applications – a stick system that offers the performance of high-rise curtain wall with the advantages of faster installation and lower field labor costs.

2250 L-R Wall System is ideally suited to curtain wall applications of four stories or less and may also be used in punched openings and ribbon windows.

Economy

The less labor-intensive stick system of 2250 L-R Wall System utilizes a plastic thermal clip that engages the 2-1/4" (57.2) face member to the glass. A built-in water deflector ensures efficient moisture removal without the complication of applying additional sealants during installation. As a result, on-site construction is easier and faster, resulting in substantial savings in time and labor.



Aesthetics

The less labor-intensive stick system of 2250 L-R Wall System utilizes a plastic thermal clip that engages the 2-1/4" (57.2) face member to the glass. A built-in water deflector ensures efficient moisture removal without the complication of applying additional sealants during installation. As a result, on-site construction is easier and faster, resulting in substantial savings in time and labor.

Performance

Superior thermal and structural performance is a key aspect of Kawneer's 2250 L-R Wall System, which is tested to all major standards for curtain walls:

Air Performance	ASTM 283
Static Water Penetration	ASTM 331
Dynamic Water Penetration	AAMA 501.1
U-factor	AAMA 1503.1

Concealed Ventilation

Kawneer's GLASSvent™, a project-out concealed ventilator without sightline buildup, can be incorporated into 2250 L-R Wall System to provide high performance and simple multi-point locking features.

For the Finishing Touch

Architectural Class I anodized aluminum finishes are available in clear and Permanodic™ color choices.

Painted Finishes, including fluoropolymer, that meet AAMA 2605 are offered in many standard choices and an unlimited number of specially-designed colors.

Solvent-free powder coatings add the green element with high performance, durability and scratch resistance that meet the standards of AAMA 2604.



Southwest Bank Building, Wildwood, MO
Architect: Chiodini Associates, St. Louis, MO
Glazing Contractor: Missouri Valley Glass Co., Inc., St. Louis, MO

Note: Numbers in parentheses () are millimeters unless otherwise noted.

Kawneer Company, Inc.
Technology Park / Atlanta
555 Guthridge Court
Norcross, GA 30092

kawneer.com
770 . 449 . 5555



© Kawneer Company, Inc. 2007-2017 LITHO IN U.S.A. Form No. 17-2229
GLASSvent™ and Permanodic™ are trademarks of Kawneer Company, Inc.

