



**Trifab™ 451UT and Trifab™ 601UT
Framing Systems
Kawneer Company, Inc.**

Final Assembly: Multiple Locations North America

Life Expectancy: 40+ Year(s)

End of Life Options: Recyclable (90-95%), Landfill (5-10%)

Ingredients:

Frame: Anodized Aluminum; **Thermal & Weathering:**

Polyurethane foams; Bicyclo[2.2.1]hept-2-ene, 5-ethylidene-, polymer with ethene and 1-propene; Carbon black; Acrylonitrile-Butadiene-Styrene Copolymer; Clay; Polypropylene; Calcium carbonate; Calcium Oxide; Dicumyl-peroxide; Polyethylene; Zinc oxide; White mineral oil (petroleum); 1,4-Diazabicyclo[2.2.2]octane; Silicic acid, aluminum potassium sodium salt; Siloxanes and Silicones, di-Me, Me vinyl, vinyl group-terminated; **Fasteners:** Stainless Steel

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

KAW-0014
EXP. 01 JAN 2025
Original Issue Date: 2017

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare