

Declare.



2500 UT Unitwall™ System Kawneer Company

Final Assembly: Multiple Locations in North America

Life Expectancy: 40+ Year(s)

End of Life Options: Recyclable (85-95%), Landfill (5-15%)

Ingredients:

Frame: Anodized Aluminum; **Thermal & Weathering:** Nylon 6; Glass, oxide, chemicals; Bicyclo[2.2.1]hept-2-ene, 5-ethylidene-, polymer with ethene and 1-propene; Acrylonitrile-Butadiene-Styrene Copolymer; Siloxanes and Silicones, di-Me, Me vinyl, vinyl group-terminated; Polypropylene; Talc; White mineral oil (petroleum); Cyclotetrasiloxane, octamethyl-, reaction products with silica; Zinc sulfide (ZnS); 2-Propenoic acid, butyl ester, polymer with ethenylbenzene and 2-propenenitrile; Calcium Oxide; Carbon black; Dicumyl-peroxide; 1-Propene, polymer with ethene; **Fasteners:** Stainless Steel

Living Building Challenge Criteria: Compliant

I-13 Red List:

| | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

KAW-0024
EXP. 01 FEB 2026
Original Issue Date: 2018

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare