

PRODUCT GREEN GUIDE

250T/350T/500T Insulpour™ Thermal Entrances

This innovative product offering gives the ability to create a true thermally broken entrance system. It's an ideal solution for high-end commercial and multifamily facilities looking to improve thermal control.



RATING SYSTEMS

LEED v4 BD+C: New Construction

- EA: Optimize Energy Performance
- EA: Renewable Energy Production
- MR: Environmental Product Declarations
- MR: Sourcing of Raw Materials
- MR: Material Ingredients
- MR: Source Reduction - Lead, Cadmium, and Copper
- MR: Construction and Demolition Waste Management
- EQ: Thermal Comfort
- EQ: Daylight
- EQ: Quality Views
- EQ: Acoustic Performance

Living Building Challenge 3.1

<input checked="" type="checkbox"/> IMP 06: Net Positive Energy	<input checked="" type="checkbox"/> IMP 12: Responsible Industry
<input type="checkbox"/> IMP 07: Civilized Environment	<input checked="" type="checkbox"/> IMP 13: Living Economy Sourcing
<input checked="" type="checkbox"/> IMP 08: Healthy Interior	<input checked="" type="checkbox"/> IMP 14: Net Positive Waste
<input checked="" type="checkbox"/> IMP 09: Biophilic Environment	<input checked="" type="checkbox"/> IMP 16: Universal Access
<input checked="" type="checkbox"/> IMP 10: Red List	

WELL Building Standard

<input checked="" type="checkbox"/> 01: Air Quality Standards	<input checked="" type="checkbox"/> 28: Cleanable Environment
<input type="checkbox"/> 03: Ventilation Effectiveness	<input checked="" type="checkbox"/> 54: Circadian Lighting
<input checked="" type="checkbox"/> 04: VOC Reduction	<input type="checkbox"/> 56: Solar Glare Control
<input checked="" type="checkbox"/> 08: Healthy Entrance	<input checked="" type="checkbox"/> 61: Right to Light
<input checked="" type="checkbox"/> 11: Fundamental Material Safety	<input checked="" type="checkbox"/> 62: Daylight Modeling
<input checked="" type="checkbox"/> 12: Moisture Mgmt	<input checked="" type="checkbox"/> 63: Daylight Fenestration
<input checked="" type="checkbox"/> 14: Air Filtration Mgmt	<input checked="" type="checkbox"/> 72: Accessible Design
<input type="checkbox"/> 15: Increased Ventilation	<input checked="" type="checkbox"/> 74: Exterior Noise Intrusion
<input type="checkbox"/> 19: Operable Windows	<input type="checkbox"/> 76: Thermal Comfort
<input checked="" type="checkbox"/> 25: Toxic Material Reduction	<input checked="" type="checkbox"/> 97: Material Transparency
<input checked="" type="checkbox"/> 26: Enhanced Material Safety	<input checked="" type="checkbox"/> 98: Organizational Transparency

FEATURES

- 2-1/2" (63.5mm), 3-1/2" (88.9) or 5" (127mm) sightline
- 2-1/4" (57.2mm) depth
- High thermal performance
- Blast mitigation, hurricane resistance
- Moderate to high traffic applications

DOCUMENTS



Declare™

Document no. KAW-0025 thru 0029
Red List Free



Environmental Product Declaration

Document no. 47868332121.106.1
Product-specific Type III EPD



Material Transparency Summary

Document no. MTS090EN
Manufacturer Material Ingredient Inventory